




Solar Powered Outdoor Bollard
Automatic Operation


lix spike solar



| color | item no. | system performance |
|-------|----------|--------------------|
|-------|----------|--------------------|

| | | |
|---|----------|-------------|
|  anthracite RAL 7016 | 93093-AN | 1.1 W/65 lm |
|---|----------|-------------|

| | | |
|---|----------|-------------|
|  cool brown | 93093-CB | 1.1 W/65 lm |
|---|----------|-------------|

| | | |
|---|----------|-------------|
|  deep black RAL 9005 | 93093-BL | 1.1 W/65 lm |
|---|----------|-------------|



technical information:

LED
lithium-ion battery
1x 2600 mAh
2700K
solar panel S

operating time:

automatic switch-on at dusk
for a duration of approx. 5 hrs.

connection:

2.6 ft supply cable luminaire
(H05RN8-F 2x0.03"²)
+ 3.3 ft supply cable solar panel
(H05RN8-F 2x0.03"²)

movable

material:

luminaire: aluminum die-casting
powder-coated
+ polycarbonate matte
solar panel
head: aluminium-diecasting
powder-coated
pole: stainless steel powdercoated;
clear glass

protection class:

IP65



light direction:



mounting:

spike mount into soil or sod

Auto mode, automatically turns on at dusk
and turns off 5 hours later